

# **ULTRA-STARTER UST-2030**

#### The Safest Energy to Fly

The Ultra-Starter UST-2030 (20Ah) is a device developed by **ENERCRAFT** to improve the engine start of airplanes or helicopters, providing clean energy, extending the life of the engines and being capable of operating in any weather and environmental condition.



The **ENERCRAFT** Ultra-Starters were

developed by our technicians and engineers to offer the latest technology in energy storage, with a unique configuration and a hybrid battery, by combining the best of the LiFeMnPO4 Lithium Cells and the best of the Ultracapacitors, ensuring an unbeatable peak current with a very compact and lightweight unit.

MAIN SPECIFICATIONS OF THE ULTRA-STARTER UST-2030	
AC INPUT	Charges from Single Phase 85-264 Vac, Freq. 47/63 Hz, 2 amps
DC OUTPUT	28.5 Vdc (30.6@full charge) Peak start: 1500 Amp
	Use as GPU: up to 10 Amps
RECHARGING RATE	45 minutes from full discharge @ 25° C
TEMPERATURE RANGE	- 40° C $\leftrightarrow$ 70° C (in operation) - 50° C $\leftrightarrow$ 85° C (in storage)
DIMENSIONS	426 mm x 327 mm x 236 mm
WEIGHT	13 kg (including cable and AN2551)
CABLE	1.5 mts Standard 3 PINS NATO AN2551 (50mm <sup>2</sup> )
PROTECTION	Electronic sensors & Fuses
COOLING	Cooling air system integrated into the equipment





# **MAIN FEATURES**

**ENERCRAFT** innovative design

First to incorporate Lithium & Ultracapacitor technology Full operation in any weather and environmental condition Peak current is ensured, even in non-ideal charge conditions Extends & preserves the aircraft main battery useful life

Provides clean energy and a more efficient engine start

True DUAL UNIT. Works as a Starter and as a GPU (10 Amp)

Supports more engine starts without recharge

### Incorporates the latest technology



IEC 61000 & IEC 60335-1 UN38.3 Meets ICAO / IATA regulations



Full data display



USB

Voltage and Battery load % **USB** connector





Reliable waterproofing (IP67 & IEC 60529) NANUK<sup>®</sup>'s latching system (MIL-STD-810F) Impact resistant (ATA Specification 300) Robust (ASTM D4169 DC-18)

#### **Portable equipment**



Lightweight unit "All in one" concept **One-handed operation** Spring loaded handle Reinforced metal padlock holes



ENERCRAFT INNOVATIVE ELECTRIFICATION TECHNOLOGY S.L. Cambados, Pontevedra - GALICIA, SPAIN / VAT: ESB02707628

> ©ENERCRAFT - ALL RIGHTS RESERVED More information: www.enercraft.eu

